Automatic Pressure Booster System





DESCRIPTION

C.R.I. Automatic pressure booster systems comprises of Self priming Jet pump (JTS / JTC - Series), Pressure tank, Mechanical Pressure switch & other accessories designed ingeniously for delivering optimal performance. This system eliminates the need of over-head tanks & float switch. The electro mechanical control device switches ON & OFF the pump automatically whenever the pressure reaches the minimum and maximum preset levels. It maintains uniform pressurized water in the pipelines suitable for all domestic applications.


FEATURES

• Sets free from operating the pump every time manually • Eliminates need of overhead tank & float switch • Ensures uninterrupted water supply with adequate pressure always • Saves water, electricity & time • Designed for easy installation

APPLICATION

For all pressure boosting applications in Houses, Multi-storeyed Apartments, Villas, Gardens, Commercial centers, Hotels, Restaurants, etc.,

DIMENSIONAL DETAILS



MODEL	Dimer in r	nsions nm	Weight in kg	
	Н	H1	iii kg	
P24-JTS-3/05M	428	495	14.5	
P24-JTS-3/07M	452	540	15.5	

^{*} All Dimensions are in mm.

PERFORMANCE DETAILS

Pressure Booster System with Stainless Steel Pumps

MODEL	TANK CAPACITY in Its	MO ⁻ POV		Inlet & Outlet	Head (Suc) in m	l/s	0.42	0.61	0.66	Pressure switch setting (bar)		Pressure level in
		kW	HP	Size in Inches		m³/h	1.5	2.2	2.4	ON	OFF	pressure tank (PSI)
P24-JTS-3/05M	24	0.55	0.75	1 x 1	7	d in tres	25	22	19	1	2.5	15 - 18
P24-JTS-3/07M	24	0.75	1.0	1 x 1	7	Head metre	31	28	25	2.1	3.5	15 - 18

MODEL	TANK CAPACITY in Its		MOTOR In		Head	I/s	0.42	0.61	0.66	Pressure switch setting (bar)		Pressure level in
		kW	HP	Size in Inches	(Suc) in m	m³/h	1.5	2.2	2.4	ON	OFF	pressure tank (PSI)
P24-JTB-3/05M	24	0.55	0.75	1 x 1	7	Head in metres	27	23	22	1.4	2.8	15 - 18
P24-JTB-3/07M	24	0.75	1.0	1 x 1	7	Head	33	29	26	2.1	3.5	15 - 18

The above models can be supplied with 60 ltrs tank also.